

For more information please call
231-399-0700 ext. 701

Email: justin@eco-buildingproducts.com
eco-buildingproducts.com

PRODUCT DATA SHEET

MONOCOAT

Hybrid Exterior Wood Protector

DESCRIPTION:

RMC Hybrid Wood Protector is a VOC free ecological protective coating for new and weathered wood. It protects against fading and wood rot of siding, decks, shutters, portals, garden furniture, etc. The oil contains UV blockers and mold inhibitors. The application is done with one layer. Easy to maintain – renovation without sanding. Does not form a film layer. Does not flake.

GENERAL GUIDANCE:

Hybrid Wood Protector can be used with any wood type (exotic wood, soft wood, thermally treated wood, etc.). **Never apply in direct sunlight and at temperatures under 50°F or over 85°F.** Only work when weather conditions are dry. Do not cover and do not place heavy objects on the wood until completely dry. Close the packaging thoroughly after use and protect from direct sunlight, frost and moisture. Never dilute.

TECHNICAL CHARACTERISTICS:

Physical state: liquid
Smell: linseed oil
Volume: 0.95 – 1.3 kg/l
VOC: 0 g/l

Colors: Pure, Natural, Teak, Grey, Royal, Chocolate, White & Black.
QUV: tested according to the EN 927-6 norm.
Complies with the toy safety norm: EN 71-3.

PACKAGING:

100 ml., 1 liter

STORAGE:

The product can be stored for up to 12 months in dry conditions and when stored in the original packaging.

Usage:

exterior wood: +/- 300 s.f./liter

ATTENTION:

Remains of previous treatments that were not carried out with Monocoat Oil must be completely removed. The preparation always has to be done with RMC products.

1. PREPARATION

Wet the wood. With a solution of water & RM Ext. Wood Cleaner clean the surface with a medium hard brush or buffer with a black pad. Then rinse thoroughly and allow to dry 24 to 36 hours. **Moisture content should be 14% or less** before applying the oil finish. **(This process must be done on new or old wood)**
Usage of RM Exterior Wood Cleaner: 1 liter = +/- 150 s.f.

2. APPLICATION

Stir the oil. Apply a thin layer with a brush or buffer with a red pad. Leave for 10 minutes then brush the surface again with the brush or red pad & buffer without adding more oil. After 5 minutes wipe all oil residue from the surface with a cloth or buffer & white pad & leave to dry.

The finish is water resistant after 24 to 36 hours and ready for use after 48 hours.

3. MAINTENANCE

Normal Maintenance with Monocoat Surface Care Spray

For periodic cleaning use Surface Care Spray to clean the surface, then rinse the surface with water.

RMC Hybrid Wood Protector

When the color starts to fade, repeat steps 1 and 2 (preparation and application) of these instructions. **On decking maintenance should be done annually.**

Cloths that are drenched with oil can combust spontaneously. Therefore you should immerse them in water after use.

[More Rubio Specs](#)