Polywhey® MVP

Sport Floor Finish

The new standard in sport floor finishes

- A superior, high gloss, single component finish created exclusively for use on gymnasiums and other hardwood sport floors.
- Formulated to achieve outstanding mar, scratch, and slip resistance with less than 95 g/L VOCs, offering uncompromising performance and durability.
- A true game changer, MVP contains no carcinogens, has a neutral odor and lets a gym floor be refinished in as little as a day without having to vacate the building.



VERMONT NATURAL COATINGS, INC
TEL: 802.472.8700
TOLL FREE: 888.639.9439
info@vermontnaturalcoatings.com
vermontnaturalcoatings.com
@ Vermont Natural Coatings, 2016

Visit www.vermontnaturalcoatings.com for videos, instructions, technical data, safety information, case studies, and more.

PolyWhey® is a registered trademark of Vermont Natural Coatings, Inc.



PolyWhey MVP Professional Sport Floor Finish

FEATURES & BENEFITS Formulated for use on gymnasium and other hardwood sport floors Superior durability, slip resistance, and ability to resist discolaration

- Superior durability, slip resistance, and ability to resist discoloration in high traffic areas
- At 95 g/L, MVP Sport Floor with PolyWhey complies with all US and Canadian VOC regulations and is safe for all environments
- Neutral odor allow for coating in occupied schools and spaces while building is in use
- Fast drying time offers the ability to apply 3 coats in one day
- Excellent flow and leveling results in easy application and beautiful finished floors
- Single-component formulation means no wasted finish
- Safe application: No cancer, no fires, and soap & water clean-up

AVAILABILITY

UPC-A	DESCRIPTION	QTY/PK	PKS/CS	CASE WT. (LBS.)	CASE DIMENSIONS			
Vermont Natural Coatings Sport Floor Finish								
076607 68154 6	1 Gallon	4	1	38	11" x 14.5" x 10"			
076607 68155 3	5 Gallon	1	1	45	15" x 12" x 12"			

REPORT CARD

			PolyWhey MVP Sport Floor	Bona® SuperSport One	Hydroline Plus w/crosslinker		
	Test						
PERFORMANCE	Taber performance: How localized abrasion wears through a coating	<50 mg loss per 100 cycles	Pass	Pass	Pass		
	Black heel mar: How a coating resists discoloration and damage from daily foot traffic	Excellent	Excellent	Excellent	Excellent		
	Sanding properties: Dried film doesn't gum, roll or pull	Pass/Fail	Pass	Pass	Pass		
	Coefficient of friction: Ratio of force of friction between two objects and force pressing them together	Between .5 and .7	Pass	Pass	Pass		
	Chemical resistance: Will household chemicals cause any softening, whitening or loss of gloss	Resistant	Pass	Pass	Pass		
SAFETY AND VALUE	Characteristic						
	VOC in grams per liter		95	145	275		
	Whey Technology		Yes	No	No		
	Contains mutagen NMP		No	No	Yes		
	Renewable content		Yes	No	No		
	Coverage		600-700	500-600	600-800		
SAF	Clarity		Water clear	Clear	Slightly amber		
	Made in USA		Yes	No	Yes		
				STATES THE REAL PROPERTY OF THE PROPERTY OF T	*All testing done by 3rd part		

What customers are saying about PolyWhey MVP Sport Floor Finish:

The primary things we're concerned about with gym floor finish is its durability, ease of maintenance and slip resistance. We're all very pleased with the MVP Sport Floor, from our maintenance staff to the basketball coaches. It's passed every test with flying colors."

- Jeff LeCours, Hardwick School District

VERMONT NATURAL COATINGS, INC
TEL: 802.472.8700
TOLL FREE: 888.639.9439
info@vermontnaturalcoatings.com
vermontnaturalcoatings.com
© Vermont Natural Coatings, 2016

Visit www.vermontnaturalcoatings.com for videos, instructions, technical data, safety information, case studies, and more.

PolyWhey® is a registered trademark of Vermont Natural Coatings, Inc.



Basic EasyStreet®