





## Sun Warden<sup>™</sup>

Sun Warden prevents discoloration and darkening caused by UV light without changing the natural appearance of the wood. For use on ceilings, floors, furniture, cabinets and walls.





## VERMONT NATURAL COATINGS°

# BÖHME

**SUN WARDEN** 



An innovative product for maintaining a non-yellow appearance on white woods.

#### **RECOMMENDED USES:**

Ideal for UV protection for new or bare interior wood





Available in Quart, Gallon, Five Gallon and Drums

- · For all interior wood surfaces
- Superior anti-yellowing technology
- Enhanced water and chemical resistance
- · Clean up with soap and water



All Vermont Natural Coatings products meet the strictest environmental standards in all 50 states and Canada.

### PREPARATION & APPLICATION



**SURFACE PREPARATION:** Surfaces must be thoroughly cleaned and dried. For use on untreated new or bare interior wood.

#### APPLICATION:



- 1) Stir well prior to use.
- 2) Always test the finish on a sample piece of wood to confirm the desired appearance.
  For best results apply in temperatures between 60°-80°F and relative humidity of



3) Apply with brush, paint pad, roller or spray on untreated or bare wood.



4) Two coats recommended.



- 5) Apply evenly with the grain and always maintain a wet edge.
- (6-12 Hr
- 6) Product will be ready for second coat after 6-12 hours depending on conditions.
  One gallon will cover approximately 300-400 sq. ft. depending on porosity of wood

#### **TECHNICAL DATA**



Milky White
Semi-Transparent
No visual defects
Coating: 30g/L (wet)
None
Do not freeze
12 months from date of manufacture
6-12 hours
Soap and water
Neutral
One week

300 -400 sq. ft. per gallon

Untreated, naturally aged wood

**Vermont Natural Coatings, Inc** info@VermontNaturalCoatings.com (802) 472-8700 Find us on **f** 

Treated with Sun Warden